

ACCESSORIES

Accessories are included in all complete profile systems; depending on application and installation.

GENERAL ACCESSORIES



SURFACE MOUNT
Ø80 × H22mm

Available in anodised aluminium, black or white



RECESSED
Ø80 × H20mm (3mm exposed)

Available in anodised aluminium, black or white




SUSPENSION WIRE WITH BASE
4 METRE CABLE

Available in anodised aluminium, black or white. Max. distance of 2m between suspension wires.




CLEAR FLEX CABLE


JOINER ACCESSORIES



STRAIGHT



90° CORNER



120° CORNER



VERTICAL TO HORIZONTAL

END CAPS



End caps are available for all profiles except for FIREFLY 13.

For profiles which come in anodised aluminium, black or white, matching end caps are also available.

CHARGE 73/105 & REIGN 75/110 ACCESSORIES



ROD SUSPENSION - SURFACE OR FLUSH MOUNT

Comes in silver. Available in black or white on request. Max. distance of 2m between suspension rods.



ADJUSTABLE ROD SUSPENSION - SURFACE OR FLUSH MOUNT

Adjustable angle for sloped ceiling. Comes in silver. Available in black or white on request. Max. distance of 2m between suspension rods.

STORM 37 & REIGN 75/110 ACCESSORIES



Y SUSPENSION WIRE WITH BASE
4 METRE CABLE

Anodised aluminium. Max. distance of 2m between suspension wires.

FLARE 33 ACCESSORIES



MOUNTING CLIP PAIR

Pair required every 600mm of profile length



SEISMIC SAFETY WIRE

Minimum of two wires per installation.

MOUNTING CLIP ACCESSORIES



FIREFLY 13
SPRING STEEL
45° MOUNTING CLIP



LUNAR 15 / HORIZON 15
CORNER MOUNTING CLIP